



Master-Grip Hose Clamp, screwable

Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO

Product Details

Construction / Material

- Specification of the connection solution: largely tension-resistant and largely leak-proof connection due to bridge profiles
- Clamp Design: clamp with housing, worm thread and clamping screw, clamping screw in sizes M5-M10 designed as slotted hexagon screw, clamp band with single or multiple bridges, spot welded bridge
- Material of the clamp: steel

Properties

- Chemical Properties: rust-protected
- Other: easy to assemble

Operating Temperature

Delivery Information

Application Areas

Customizing Options

Article Variants

Article number	DN of the hose mm	Type	Clamping range mm
001626	35/40	for right-handed hoses in DN 35/40	35 - 55

Article number	DN of the hose mm	Type	Clamping range mm
001629	45/50	for right-handed hoses in DN 45/50	45 - 65
001633	55/60	for right-handed hoses in DN 55/60	55 - 75
001636	65/70	for right-handed hoses in DN 65/70	65 - 85
001639	75/80	for right-handed hoses in DN 75/80	75 - 95
001642	90	for right-handed hoses in DN 90	85 - 105
001646	100	for right-handed hoses in DN 100	95 - 115
001649	110/115	for right-handed hoses in DN 110/115	105 - 125
001651	120/125	for right-handed hoses in DN 120/125	115 - 135
001653	130	for right-handed hoses in DN 130	125 - 145
001655	140	for right-handed hoses in DN 140	135 - 155
001657	150	for right-handed hoses in DN 150	145 - 165
001659	160	for right-handed hoses in DN 160	155 - 175
001661	170/175	for right-handed hoses in DN 170/175	165 - 185
001663	180	for right-handed hoses in DN 180	175 - 195
001667	200	for right-handed hoses in DN 200	195 - 215
001670	215	for right-handed hoses in DN 215	205 - 225
001672	220/225	for right-handed hoses in DN 220/225	215 - 235
001674	250	for right-handed hoses in DN 250	245 - 265
001676	275	for right-handed hoses in DN 275	265 - 285
001679	300	for right-handed hoses in DN 300	295 - 315
001682	310/315	for right-handed hoses in DN 310/315	305 - 325
001684	325	for right-handed hoses in DN 325	315 - 335
001685	350	for right-handed hoses in DN 350	345 - 365
001687	375	for right-handed hoses in DN 375	365 - 385
001688	400	for right-handed hoses in DN 400	395 - 415
001691	450	for right-handed hoses in DN 450	445 - 465
001692	500	for right-handed hoses in DN 500	495 - 515
001677	280	/	275 - 280

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
masterflex.de/en

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

