



Master-Tube PA Brake

Special polyamide hose for brake and automotive applications



spiral-free

Product Details

Construction / Material

- Type of construction: extruded hose without metal spiral
- Execution of the wall: made of highly abrasion-resistant material, made of a material that is insensitive to stress corrosion cracking, made of a material with high impact strength, dimensions and tolerances correspond to DIN 73378 and manufactured according to DIN 74324

Properties

- Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to chemicals, good resistance to oil, good UV resistance, halogen-free, hydrolysis resistant, free from paint wetting impairment substances (LABS)
- Mechanical Properties: small bending radius
- Colour: black

Operating Temperature

- Temperature Range: -40 - 90

Delivery Information

- Delivery, type of production: inner diameter: 2.0 - 16.0 mm, outer diameter: 4.0 - 20.0 mm

Application Areas

- Areas of application: Automotive, Plant & Mechanical Engineering, Industry, Sea & Rail transport, Cable manufacturers, Vehicle Construction

Customizing Options

- optional item modification (on request): printable, rolls

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
masterflex.de/en

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

